



Figure A:

- 1 Side Mount
- 3 3/4" bolt circle for front shroud
- Tapped rear 3-hole 2 7/8" bolt circle
- Cord: 21" lead length with #10 ring studs

## STANDARD FEATURES

Shaded pole • 4 Pole • 1550 RPM • Totally Enclosed • 50/60 Hz • CW Rotation  
Long life lubricated Sintec sleeve bearings • Opposite shaft end  
Nuts, screws, and fan blade adapter included

Figure B:

- 3 3/4" Bolt Circle for front shroud
- No holes tapped in rear and no side mount
- Cord: 36" Length



## ELCO MOTORS

WATTS	FIGURE	VOLTS	AMPS	MODEL NUMBER	DIMENSIONS			
					H	A	B	D
4	A	115	0.36	EC-4W115	0.51"	2.82"	0.49"	1.65"
4	A	230	0.18	EC-4W230	0.51"	2.82"	0.49"	1.65"
5	A	115	0.40	EC-5W115	0.51"	2.82"	0.49"	1.65"
5	A	230	0.20	EC-5W230	0.51"	2.82"	0.49"	1.65"
6	A	115	0.41	EC-6W115	0.79"	3.05"	0.49"	1.89"
6	A	230	0.20	EC-6W230	0.79"	3.05"	0.49"	1.89"
9	A	115	0.58	EC-9W115	0.79"	3.05"	0.49"	1.89"
9	B	115	0.58	EC-9W115NF	0.79"	3.25"	0.63"	---
9	A	230	0.35	EC-9W230	0.79"	3.05"	0.49"	1.89"
16	A	115	1.00	EC-16W115	1.18"	3.60"	0.63"	2.44"
16	A	230	0.50	EC-16W230	1.18"	3.60"	0.63"	2.44"
25	A	115	1.50	EC-25W115	1.77"	4.19"	0.61"	2.40"
34	A	115	1.60	EC-34W115	1.77"	4.19"	0.61"	2.40"
34	A	230	0.80	EC-34W230	1.77"	4.19"	0.61"	2.40"

## BRACKET

MODEL NUMBER
EC-EUBKT01
<i>This mounting adapter bracket is used when replacing European style Elco motors with the above US style Elco motors</i>

## FAN BLADES

USE WITH	DIAMETER	PITCH	BLADES	APPLICATION	CONSTRUCTION	MODEL NUMBER
4 & 5W	6.06"	28*	5	SUCTION	PLASTIC	EC-4VEA012
4 & 5W	6.06"	19*	5	SUCTION	ALUMINUM	EC-4012309
4 & 5W	6.77"	28*	5	SUCTION	ALUMINUM	EC-4012543
6 & 9W	7.87"	28*	5	SUCTION	PLASTIC	EC-4VEA009
6 & 9W	7.87"	34*	5	SUCTION	PLASTIC	EC-4VEA010
9W	9.05"	25*	5	SUCTION	PLASTIC	EC-4VEA013
16W	9.05"	31*	5	SUCTION	PLASTIC	EC-4VEA006
16W	10.0"	28*	5	SUCTION	PLASTIC	EC-4VEA007



Minimum order is \$25.00

Prices are subject to availability and manufacturers price increase

Possession of this sales flyer does not constitute an offer to sell

All orders are subject to approval by our credit department