



ECM MADE EASY™

Evergreen® VS

VARIABLE SPEED REPLACEMENT MOTORS

The Evergreen VS motor and Evergreen VS user interface are designed to replace Genteg® constant airflow (variable speed) ECM indoor blower motors. The Evergreen VS product line is designed specifically to replace GE®* models 2.0, 2.5, Genteg models 2.3, 3.0 and Eon® motors (including models formerly branded GE or GE ECM by Regal Beloit). These motors represent the largest volume of variable speed motors used to date in HVAC OEM indoor blower motor applications.

FEATURES

- Pre-programmed
- Plug-n-play
- Dual voltage
- Dual rotation
- Truck stock

BENEFITS

- Two year warranty*
- Complete calls same day including after hours calls
- Reduce time on call using part on truck
- Built by same manufacturer as original motor
- Maintains system performance and efficiency

CONSTANT AIRFLOW ECM (VARIABLE SPEED) REPLACEMENT MOTOR OPTIONS

INDOOR BLOWER MOTORS

Constant Airflow (Variable Speed) ECM Motors

(Model 2.0. Gentea® models 2.3 and Eon® motors)

Note: The model 2.3 motor has the same physical appearance as the model 2.5 motor. Always confirm model name on motor.

EVERGREEN® VS MOTOR

Evergreen VS motor

REQUIRED ACCESSORY (SOLD SEPARATELY FROM MOTOR)







• The Evergreen VS User Interface (#5K010 or #5K010V) is required for this application and is installed

permanently with the motor • This part is sold separately from the



Eon[®]

Constant Airflow (Variable Speed) ECM Motors

(Model 2.5 motor)

Note: The model 2.5 motor has the same physical appearance as the model 2.3 motor. Always confirm model name on motor.







• The Genteq 16-4 Pin Adapter (#5K015) is required for this application and is installed permanently with the motor

• This part is sold separately from the motor

4-PIN SOLUTION

Model

16-PIN SOLUTION

Model



Constant Airflow (Variable Speed) ECM Motors

(Genteq model 3.0 motor)





• Plug-n-play (Connect OEM plugs...DONE)



^{*} This warranty shall expire twenty-four (24) months from first use of the Product or thirty (30) months from date of shipment of the Product, whichever occurs first. Except as stated here, Regal Rexnord standard limited warranty applies. See www.regalrexnord.com (Terms and Conditions of Sale).

EVERGREEN® VS MOTORS AND ACCESSORIES

EVERGREEN VS USER INTERFACE - 5K010V NEW



The Evergreen VS user interface (UI) #5K010V is the second generation of this product. The UI functions have been simplified for everyday installation, with all optional features moved to the Evergreen VS Optimizer™ tool. This tool can be found in the Dealer Toolbelt app available on both Apple Store™* and Google Play™*.







SPECIFICATIONS

Match the horsepower (HP) and voltage (VAC) ratings of the new Evergreen VS motor to the motor being replaced. It is not necessary for the RPM or the amperage (FLA) to match.

EVERGREEN® VS MOTORS								
STOCK #	HP	VOLTS	FLA	ROTATION	RPM	FRAME	DIM A	DIM B
6503V	1/3	120/240	5.0/2.8	CCW/CW	1050	NEMA®* 48	10.71"	5.71"
6505V	1/2	120/240	7.7/4.3	CCW/CW	1050	NEMA 48	11.21"	6.21"
6507V	3/4	120/240	10.1/6.1	CCW/CW	1050	NEMA 48	11.96"	6.96"
6510V	1	120/240	12.8/7.4	CCW/CW	1050	NEMA 48	12.71"	7.71"

-		Dim. A ——		-
-	— Dim. B –	-		
1 ledftp	771=-	- 14-	5.00	_
			0.00	
		□ -	4.50 —	-
Ø 5.58	=			=

	EVERGREEN® ACCESSORIES					
	STOCK#	DESCRIPTION	NOTE			
	5K010	Evergreen VS User Interface■	Sold separately and installed permanently with the motor.			
new	5K010V	Evergreen VS User Interface■	Sold separately and installed permanently with the motor.			
	5K015	Genteq 16-4 Pin Adapter	Sold separately and installed permanently with the motor.			
	5K016	Evergreen Rotation Reversing Harness [*]	Sold separately and installed permanently with the motor.			

^{*}The Evergreen VS User Interface (UI) is compatible with all Evergreen VS motors.

For more information on Evergreen VS motors and user interface, scan this code with your smart phone or go to www.EvergreenVS-motors.com





Regal Rexnord Corporation

1325 Heil Quaker Blvd. LaVergne, TN 37086

Customer Service: 800-672-6495 800-468-2062

www.ECMMadeEasy.com

APPLICATION CONSIDERATIONS

The proper selection and application of products and components, including the related area of product safety, is the responsibility of the customer. Operating and performance requirements and potential associated issues will vary appreciably depending upon the use and application of such products and components. The scope of the technical and application information included in this publication is necessarily limited. Unusual operating environments and conditions, lubrication requirements, loading supports, and other factors can materially affect the application and operating results of the products and components and the customer should carefully review its requirements. Any technical advice or review furnished by Regal Rexnord and/or its affiliates ("Regal Rexnord") with respect to the use of products and components is given in good faith and without charge, and Regal Rexnord assumes no obligation or liability for the advice given, or results obtained, all such advice and review being given and accepted at customer's risk.

For a copy of our Standard Terms and Conditions of Sale, please visit https://www.regalrexnord.com/Terms-and-Conditions-of-Sale. These terms and conditions of sale, disclaimers and limitations of liability apply to any person who may buy, acquire or use a Regal Rexnord product referred to herein, including any person who buys from a licensed distributor of these branded products.

*The following are believed to be the trademarks and/or trade names of their respective owners and are not owned or controlled by Regal Rexnord Corporation. Apple Store: Apple Inc.; GE: General Electric Company; Google Play: Google LLC; NEMA: National Electrical



[▲]The Evergreen VS motor will automatically configure rotation to match the application. The rotation reversing harness (#5K016) is only needed if the motor does not operate the correct direction following the installation instructions.